

REPLACING TRECO DOOR GLIDES (to suit sliding door sheds only)

(includes Victa Treco & Oldfields Treco Sliding Door Garden Sheds – one size fits all)

1. Unfasten fascia panel above doors
2. Unfasten each door panel from old glides (located at top of doors)
3. Choose a front corner panel (the most accessible one)
4. Unfasten the screws on the side wall (of the corner panel)
5. Carefully fold back the corner panel to expose the end of the front top rail
6. Cut and/or fold up the side top rail to expose the open end of the front top rail
7. Remove the old door glides from this open end
8. Assemble the door glide wheel (X9) to the door glide (X6) as per diag below
9. Insert the door glides into the front top rail with the wheel facing the inside of the shed
10. Carefully fold the corner panels back into original position and refasten screws
11. Locate the doors back into the base rail & fasten the top of the doors to the new door glides – using the middle of the 3 holes
12. Slight adjustment may be required to square up doors – if major adjustment required – use a different hole in the door glide
13. **DO NOT OVERTIGHTEN DOOR GLIDES AS THIS MAY VOID WARRANTY**
14. Apply a suitable lubricant eg silicone spray to door track upon installation & annually to maintain smooth operation of doors

To view the full “HOW TO INSTALL DOOR GLIDES VIDEO” click on link below

<http://www.trecooorglides.com.au/TDG/DoorGlideInstall.htm>

